

NEOSOFT™ 73-837

Neoprene Exam Glove with HYDRASOFT™ Moisturizing Technology



A revolution in skin moisturization with sensational grip

- Features HYDRASOFT™ Technology to rehydrate dry and cracked skin and improve overall skin condition
- Soft material provides wearers exceptional comfort and ease of use
- Neoprene formulation and textured fingers deliver a secure, reliable wet grip
- Ultra-lightweight design for enhanced tactile sensitivity



Industries

Healthcare

Recommended For

- Enhanced grip in wet environments
- Enhanced tactile sensitivity and dexterity, especially for delicate procedures
- Brief, low-risk examination procedures
- Extra comfort during long, sustained procedures
- Damp donning
- Standard patient examinations
- Protection from latex Type I allergy and minimize chemical Type IV allergies in HCW's or patients
- Helping protect skin from drying or cracking
- Brief, low-risk examination procedures
- Helping protect skin from drying or cracking
- Protection from Type I latex allergy in HCW's or patients







NEOSOFT™ 73-837

Neoprene Exam Glove with HYDRASOFT™ Moisturizing Technology

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	NEOSOFT™ 73-837
Material	Neoprene (Polychloroprene)
Color	Green
Glove Design	Polymer Coated, Textured Fingers
Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 13485, ISO 9001
Regulatory	ASTM D6977, EN 420:2003 + A1:2009, FDA21 CFR 177-2600-US Food Contact Approved, ISO 13485, ISO 9001
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Indonesia
User Needs Segment	High Touch
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	No

PHYSICAL PROPERTIES

	Typical	Typical Values		
Length (mm/inches)	240	240 / 9.5		
Freedom from Holes (Inspection level I)	1.5 <i>A</i>	1.5 AQL		
Palm Thickness (mm/mils)	0.07	0.07 / 2.8		
Finger Thickness (mm/mils)	0.09	0.09 / 3.5		
	BEFORE AGING	AFTER AGING		
Ultimate Tensile Strength (MPa)	≥ 14	≥ 14	ASTM D412 & D573	
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412	

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	73837060	73837070	73837080	73837090	73837100

Technology



Performance Standards and Regulatory Compliance





SO 13485 ISO 900

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699 North America Region

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region
Ansell Commercial Mexico S.A. de C.

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

