

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

1 Identification

- · Product identifier
- · Trade name: UniFil Bond (Self-Etching Primer)
- Relevant identified uses of the substance or mixture and uses advised against

Dental material

The product is intended for professional use.

To avoid risks for humans and environment obtain instructions.

- · Application of the substance / the mixture Dental bonding material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

- · Information department: Regulatory Affairs
- · Emergency telephone number:

During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Lig. 2 H225 Highly flammable liquid and vapor.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Eye Irrit. 2B H320 Causes eye irritation.

· Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms









GHS02 GHS05 GHS07

· Signal word Danger

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 1)

· Hazard-determining components of labeling:

ethyl alcohol

2-hydroxyethyl methacrylate (HEMA)

· Hazard statements

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

Causes eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dusts or mists.

Wear protective gloves / eye protection / face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

15 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

· Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable.

· **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

٠	D	a	n	g	e	ro	us	6	cor	np	on	ents	:

64-17-5	ethyl alcohol	25-50%
868-77-9	2-hydroxyethyl methacrylate (HEMA)	1-5%

(Contd. on page 3)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 2)

· Additional information:

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

· After eye contact:

Protect unharmed eve.

Rinse opened eye for several minutes under running water. Then consult a doctor.

Call a doctor immediately.

After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources

Avoid contact with the eyes and skin.

Wear protective clothing.

(Contd. on page 4)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 3)

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralizing agent.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Observe instructions for use.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Observe instructions for use / storage.

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

64-17-5 ethyl alcohol

PEL Long-term value: 1900 mg/m³, 1000 ppm REL Long-term value: 1900 mg/m³, 1000 ppm TLV Short-term value: 1880 mg/m³, 1000 ppm

(Contd. on page 5)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 4)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- **Breathing equipment:** Suitable respiratory protective device recommended.
- Protection of hands: Protective gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Safety glasses

9 Phy	vsical	and c	hemical	pro	perties

· Information on basic physical and · General Information	chemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Aromatic
· Odor threshold:	Not determined.
· pH-value at 20 °C (68 °F):	1
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 64 °C (> 147 °F)
· Flash point:	13 °C (55 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Undetermined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	3.5 Vol %
Upper:	15.0 Vol %
· Vapor pressure:	Not determined.
	(Contd. on page 6)

(Contd. on page 6)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 5)

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 41.8 %

 Water:
 40.0 %

 VOC content:
 41.8 %

• Other information No further relevant information available.

10 Stability and reactivity

- · **Reactivity** No further relevant information available.
- · Chemical stability Stable at ambient temperature.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: No further relevant information available.
- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: Sensitization possible through skin contact.
- Experience with humans:

May cause damage to central nervous system.

May cause damage to liver.

May cause damage to lungs.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 6)

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Corrosive Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
ethyl alcohol	1
butylated hydroxytoluene (BHT)	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

· Carcinogenic categories' legend:

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

Additional carcinogenic information:

The substance ethyl alcohol, also known as ethanol, is listed by IARC as a Group 1 carcinogen but in alcoholic beverage consumption. IARC Volume 100E (2012) "Personal Habits and Indoor Combustions" stated in its monograph "Consumption of Alcoholic Beverages" the following evaluation: "Ethanol in alcoholic beverages is carcinogenic to humans (Group 1)." GC products are not consumable alcoholic beverages.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

(Contd. on page 8)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

· Other adverse effects No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1170
UN proper shipping nameDOTADRIMDG, IATA	Ethanol solutions 1170 Ethanol solutions (Ethyl alcohol solutions) ETHANOL SOLUTION
· Transport hazard class(es)	
· DOT	
FLAMMAR, E 1/01/0	
· Class	3 Flammable liquids
· Label	3
ADR	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
Label	3
· Packing group · DOT, ADR, IMDG, IATA	II
	(Contd. on page

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

	(Contd. of page
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	F-E,S-D
Transport in bulk according to Anne	x II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1170, Ethanol solutions (Ethyl alcohol solutions), 3, I

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture · SARA (Superfund Amendments and Reauthorization Act)
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

ethyl alcohol

2-hydroxyethyl methacrylate (HEMA)

water, distilled

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

ethyl alcohol A3
butylated hydroxytoluene (BHT) A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Printing date 02/27/2015 Version US-EN-Rev 1 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 9)

· Hazard pictograms









GHS07 GHS02 GHS05

· Signal word Danger

· Hazard-determining components of labeling:

ethyl alcohol

2-hydroxyethyl methacrylate (HEMA)

Hazard statements

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

Causes eve irritation.

May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dusts or mists.

Wear protective gloves / eye protection / face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

- Department issuing SDS: Regulatory Affairs
- Contact:

Regulatory Affairs

Telephone No. +1 (708) 597-0900

sds@gcamerica.com

· Date of preparation / last revision 02/27/2015 / -

· Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HCS: Hazard Communication Standard (USA)

MSDS: Material Safety Data Sheet

SDS: Safety Data Sheet

ECHA: European Chemicals Agency

OSHA: Occupational Safety and Health Administration (USA)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

Version US-EN-Rev 1 Printing date 02/27/2015 Reviewed on 02/27/2015

Trade name: UniFil Bond (Self-Etching Primer)

(Contd. of page 10)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Sources

- Manufacturers' MSDSs/SDSs
- OSHA (https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html)
- TOXNET (http://toxnet.nlm.nih.gov/)
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

· Notes:

CAS Registry Number is a Registered Trademark of the American Chemical Society. CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

* Data compared to the previous version altered. This version replaces all previous versions.

· Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.